


건축물 및 기타사항에 관한
지구단위계획결정(변경)도

Figure 2 displays 18 examples of various types of road pavement, categorized into three groups of six. Each example consists of a small diagram showing the pavement pattern and a corresponding text label in Korean.

- Group 1 (Top Row):**
 - 대지불활가능성 (Large area non-activation possibility)
 - 건축지정선 (Building designation line)
 - 1층 벽면지정선 (1st floor wall designation line)
- Group 2 (Middle Row):**
 - 건축한계선 (Building limit line)
 - 최고중배지구간 (Maximum double lane spacing)
 - 저중배지구간 (Low double lane spacing)
- Group 3 (Bottom Row):**
 - 중중배지구간 (Medium double lane spacing)
 - 통경구간 (Through section)
 - 연도형배지구간 (Year-type double lane spacing)
- Group 4 (Bottom Row):**
 - 공공도행통로 (Public pedestrian passage)
 - 지랑진흙일몰이구간 (Gutter mud removal section)
 - 직각배지구간 (Right-angle double lane spacing)
- Group 5 (Bottom Row):**
 - 공개공지 (Public notice)
 - 지구단위계획구역 (Local unit planning area)
 - 공동주택의 주택유형 구분 (Apartment type classification)
- Group 6 (Bottom Row):**
 - 숙박시설설치 불허구간 (Prohibited area for accommodation facility installation)
 - 아케이드설치구간 (Arcade installation section)
 - 어닝/자양설치구간 (Awning/soil installation section)

Additional information provided in the diagram:

- ※ 주택유형 : a: 60㎡ 이하, b: 60㎡~85㎡ 이하, c: 85㎡ 초과

[illegible]

Scale = 10,000

